

Anchor ProLink™ Intercom Patent Pending

ProLink™ is a digital wireless intercom system that is easy to set-up and easy to operate. The system allows full duplex communication with one master belt pack and three remote belt packs without the need for a base station.

All four belt packs can communicate in "Always On" mode which is just like talking on a telephone. This allows you to continue working with your hands while using the intercom. This is particularly important for emergency response teams and evacuation coordinators. "Push to Talk" mode is also available with the flip of a switch. Applications such as directors or coaches who only want to broadcast selected instructions tend to prefer "Push to Talk."

This patent pending intercom has a range of 250' through walls and glass. The digital design and performance of ProLink will surely impress you. Take a system out for a test drive today - just email us at prolink@anchoraudio.com.

BELT PACK



COMPONENTS

- BP-9000M** Master Belt Pack
- BP-9000R** Remote Belt Pack
- BP-9000L** Listen Only Belt Pack
- E-9000** Encryption Installation
- H-2000** Dual Ear Muff Headset
- H-2000S** Single Ear Muff Headset
- H-2000L** Dual Ear Muff Headset - Listen Only
- H-2000LS** Single Ear Muff Headset - Listen Only
- GC-9000** Gang Charger
- HC-1600PL** Pelican Hardcase w/Pick 'n Pluck Foam

PACKAGE

Pro-40

Four User Package:

- 1 - BP-9000M Master Belt Pack
- 3 - BP-9000R Remote Belt Packs
- 4 - Headsets
(H-2000 or H-2000S)
- 1 - GC-9000 Gang Charger
- Lightweight, high-density card board case



TECHNICAL SPECS

ProLink Belt Pack (BP-9000)

RF Frequency Range	902-928MHz
Modulation	FSK
Range (line of sight)	Duplex 250' / 75 m
Antenna	1/2 - wavelength dipole
Power Supply	9VDC, 1.2ADC
Battery Life	15 hours
Weight	15oz. / 0.42kg (w/ batteries)
Dimensions	4.5 x 6.25 x 3.75" / 114.3 x 158.75 x 95.25 mm

Single-Ear (H-2000S) & Dual-Ear Headphones (H-2000)

Drivers	Dynamic, 40mm
Impedance	300ohm +/- 15%
Frequency Response	20Hz - 20kHz
SPL	91dB +/- 3dB
Rated Power	> 40mW
Distortion	< 5%
Microphone	Dynamic, Uni-directional, Low impedance
Mic Sensitivity	Referenced to 0dB=1V/μbar, 1kHz
Frequency Response	Min -85 dB / Typical -83 dB / Max -81 dB
Connector Plug	200Hz-12kHz
Weight	4-pin XLR, female Single: 13 oz. / 0.37 kg & Dual: 16 oz. / 0.45 kg



FCC ID: J8ZBP-9000



(FEATURES & SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE)

TWO YEAR WARRANTY



Anchor Audio, Inc.
Portable Sound Systems • Torrance, California

800.262.4671
www.anchoraudio.com

S-PL/0410