

Accessories

CABLES

MAC - Microphone Cable Assembly

- For handheld models HCU350, HDU250, HDU150, & HDO100
- Female XLR to stripped and tinned wires
- 25' cable
- 2-conductor plus shield

XLR25 - Microphone Cable

- For handheld models HCU350, HDU250, HDU150, & HDO100
- Male XLR to female XLR
- 25'
- 2-conductor plus shield

CLIPS

MC22 - Handheld Clip

- For instrument microphone HCU350
- Black, flexible, impact-resistant plastic

MC27 - Handheld Clip

- For HDU250, HDU150, and HDO100
- Black, flexible, impact-resistant plastic

WINDSCREENS

WSGCU250 - Windscreen for GCU250

- Foam windscreen for use with GCU250 microphone

WSHCU350 - Windscreen for HCU350

- Foam windscreen for use with HCU350 microphone



MC27

MC22



WSGCU250



WSHCU350



MAC



XLR25



SF4

SB6



MSM



DS3

MFM

MOUNTS

MFM - Flange Mount

- 3-pin female XLR connector non-shock-isolated
- 3 $\frac{1}{4}$ " H x 1 $\frac{3}{4}$ " dia. base, 3 ounces

MSM - Shock-Isolated Microphone Base

- For GCU250 and GDU150
- Provides superior mechanical noise and vibration isolation
- Lightweight ABS material housing
- XLR (female) connector
- Thick shock-absorbing rubber cushion
- Ideal fixture for boardrooms, conference rooms, pulpits, podiums, and newsrooms
- 4 $\frac{3}{4}$ " W x 1 $\frac{3}{4}$ " H x 4" D, 6 ounces

STANDS

DS3 - Desk Stand

- 3" chrome-finish tube
- 6" diameter cast iron base, 3 lb.

SF4 Floor Stand

- 34" to 62" adjustable height
- Round 10" diameter die cast base, 9 lb.
- Grip-action clutch and chrome-plated tubing

SB6 - Floor Boom Stand

- Telescopic floor stand
- Sliding 30" boom arm
- 34" to 62" adjustable height, 6 lb.
- Chrome-plated tubing
- Tripod base