

Microphone Accessories

Stands

SF4 - Floor Stand

- 34" to 62" adjustable height
- Round 10" diameter die cast base, 9 lb.
- Grip-action clutch and chrome-plated tubing

SB6 - Floor Boom Stand

- Telescopic floor stand
- Sliding 30" boom arm
- 34" to 62" adjustable height, 6 lb.
- Chrome-plated tubing
- Tripod base

DS3 - Desk Stand

- 3" chrome-finish tube
- 6" cast iron base, 3 lb.



Mounts

MFM - Flange Mount

- For use with gooseneck models GCU250 & GDU150
- 3-pin female XLR connector, non-shock-isolated
- 3-1/4" H x 1-3/4" dia. base, 3 ounces



MFM

MSM - Shock-Isolated Microphone Base

- For use with gooseneck models GCU250 & GDU150
- Provides superior mechanical noise and vibration handling
- Lightweight ABS material housing
- XLR (female) connector
- Thick shock-absorbing rubber cushion
- Ideal fixture for boardrooms, conference rooms, pulpits, podiums, and newsrooms
- 4-3/4" W x 1-3/4"H x 4" D; 6 ounces



MSM

Windscreens

WSGCU250 - Windscreen for GCU250 Microphone

- Foam windscreen for use with GCU250 microphone

WSGCU250
WSHCU350

WSHCU350 - Windscreen for HCU350 Microphone

- Foam windscreen for use with HCU350 microphone

Cables

MAC - Microphone Cable Assembly

- For use with handheld models HCU350, HDU250, HDU150 & HDO100
- Female XLR to stripped and tinned wires
- 25' cable
- 2-conductor plus shield



MAC

XLR25 - Microphone Cable

- For use with handheld models HCU350, HDU250, HDU150 & HDO100
- Male XLR to female XLR
- 25' cable
- 2-conductor plus shield



XLR25

Clips

MC22 - Handheld Clip

- For use with instrument microphone HCU350
- Black, flexible, impact-resistant plastic



MC22

MC27 - Handheld Clip

- For use with HDU250, HDU150, and HDO100
- Black, flexible, impact-resistant plastic



MC27