

# Easy Design™ Horn Loudspeakers

## Model HS15EZ



---

### Description

The Bogen HS15EZ horn loudspeaker is a compact, high intelligibility, reentrant type loudspeaker designed for use with 70V amplifier systems. Its sturdy, weatherproof, all metal construction is ideal for indoor and outdoor use in industrial plants, warehouses, schools, construction sites, transportation terminals, and recreational areas.

The HS15EZ is a 15-watt single-tap speaker with stepped volume control. The HS15EZ comes with a swivel and tilt mounting base for greater flexibility in setting the angle of projection. Engineered to simplify installation (with a uniquely designed all-purpose mounting bracket) and field maintenance (with a self-aligning, field replaceable diaphragm), the HS15EZ saves both time and money. Both the speaker and the mounting bracket are attractively finished in textured mocha enamel.

---

### Features

- 15W power handling
- Screw terminal connections for fast installation
- Single-tap design
- Works with 70V amplifier outputs
- Stepped attenuator volume control
- Swivel and tilt mounting base for flexibility in coverage
- High intelligibility and efficiency
- Weatherproof, all metal construction
- I-beam mounting clamp (optional)



Specifications subject to change without notice.  
© 1999 Bogen Communications, Inc.  
Part No. 54-8004-01 Printed in U.S.A. 9909

---

<b>Technical Specifications</b>	<b>Power Rating (RMS):</b>	15 watts continuous
	<b>Frequency Response:</b>	275Hz to 14kHz
	<b>Impedance:</b>	326 ohms (for use on 70V amplifier outputs)
	<b>Sound Pressure Level:</b>	121dB @ 4 ft. on axis with 15 watt input@1000Hz
	<b>Dispersion:</b>	110°
	<b>Dimensions:</b>	9" Diameter x 9-1/4" Depth (22.9 x 23.5cm)
	<b>Shipping Weight:</b>	5 lbs.
	<b>Finish:</b>	Textured mocha enamel

---

**Architects and Engineers Specifications**

The loudspeaker shall be a Bogen Model \_\_\_\_ (HS15EZ), or approved equivalent, reentrant type horn loudspeaker. The frequency response shall be 275Hz to 14kHz. Rated power output shall be 15 watts, RMS continuous. Dispersion shall be 110°. Sound pressure level, measured four feet on axis with 15 watt input @ 1000Hz, shall be at least 121dB.

The unit shall have an impedance of 326 ohms.

The loudspeaker shall be of weatherproof, all metal construction, with driver enclosed within a waterproof housing. The loudspeaker shall include a self-aligning, field-replaceable diaphragm.

Screw terminals shall be provided for connection to the audio line. A plastic cover shall be provided to protect the connectors and stepped volume control, and provide strain relief for the audio line.

An all-purpose mounting bracket shall provide precise positioning in the vertical and horizontal planes with a single adjustment. The bracket shall include banding slots to permit mounting the loudspeaker on beams or pillars. Bracket and loudspeaker shall be finished in textured mocha enamel. The unit shall measure 9" diameter by 9-1/4" depth. Shipping weight shall be 5 lbs.

**BOGEN**<sup>®</sup>  
COMMUNICATIONS, INC.

50 Spring Street, Ramsey, New Jersey 07446  
201-934-8500, Fax: 201-934-9832, Web Site: www.bogen.com