

Easy Design™ Wall Baffle Speaker

Model WB1EZ



Description

The Bogen WB1EZ Wall Baffle Speaker is an 8" cone speaker enclosed in a simulated walnut-finished wooden enclosure with a black grille cloth on front.

Designed for easy wall-mount installation, the WB1EZ comes pre-assembled.

The WB1EZ is a 1-watt single-tap speaker with recessed volume control designed for use in 70V amplifier systems.

Features

- Features screw terminal connections for fast wire lead connection
- 1W single-tap design
- Works with 70V amplifier outputs
- High intelligibility and efficiency
- Walnut vinyl finish
- Designed for easy wall-mount installation
- 8" cone speaker
- Wooden cabinet
- Recessed volume control



Specifications subject to change without notice.
© 1999 Bogen Communications, Inc.
Part No. 54-7886-01 Printed in U.S.A. 9910

Technical Specifications	Power Rating (RMS):	1-watt, continuous
	Frequency Response:	50Hz to 12kHz
	Impedance:	4900-ohms (for use on 70V amplifier outputs)
	Sound Pressure Level:	95dB at 4 ft. with a 1-watt input on axis
	Dimensions:	9-1/2" W x 9-1/2" H x 5-1/4" D (3-1/4" D @ bottom)
	Shipping Weight:	19 lbs.
	Finish:	Walnut Vinyl

Architects and Engineers Specifications	<p>The surface mounting loudspeaker shall be a Bogen Model WB1EZ, or equivalent, eight inch cone-type loudspeaker having a frequency response of at least 50Hz to 12kHz. The on axis sound pressure level shall be 95dB, at least four feet with one-watt input. The loudspeaker shall have a six-ounce ceramic magnet and a 3/4-inch voice coil.</p>	<p>Glue blocks shall be used to reinforce all side corner joints. The speaker opening shall be covered with a black grille cloth.</p>
	<p>The loudspeaker shall be assembled in a wall baffle for surface-mounting, angled for additional downward sound dispersion. The baffle shall be constructed of 3/8" particle board, glued and covered in simulated walnut vinyl.</p>	<p>Overall dimensions shall be 9-1/2" W x 9-1/2" H x 5-1/4" D [top] (3-1/4" D base).</p>